


EcoCycle

PORCELAIN STONE

- 8 earth-toned colors
- Stone-look exudes a feeling of rustic elegance
- Ideal for all types of commercial and residential applications
- Cost-effective and environmentally responsible
- Contributes to the efforts of companies seeking LEED certification of new buildings and major renovations
- Available only from Crossville



EC114 Grand Canyon




EC101 Wetlands




EC102 Marshland



EC103 Earth



EC116 Plymouth Rock



EC104 Pine Barren



EC105 Night Air



EC001 Storm
8" x 8" Cross-Sheen 8" x 8" Cross-Tread

Sizes Available

Nominal	Size Actual	Size Metric (cm)	Thickness
8" x 8"	7-3/4" x 7-3/4"	19.6 x 19.6	5/16"
12" x 12"	11-3/4" x 11-3/4"	29.8 x 29.8	5/16"


*EC001 only

Trim Sizes

Nominal Size	Actual Size	Metric (cm)	Thickness
4" x 12" Single Bullnose	3-3/4" x 11-3/4"	9.5 x 29.8	5/16"
6" x 12" Cove Base	5-7/8" x 11-3/4"	14.6 x 29.8	5/16"



4" x 12" Single Bullnose



6" x 12" Universal Cove Base

Trim Sizes (EC001 only)

Nominal Size	Actual Size	Metric (cm)	Thickness
6" x 8" Cove Base	5-7/8" x 7-3/4"	14.9 x 19.7	5/16"
6" x 8" Cove Base Corner Left	5-7/8" x 7-3/4"	14.9 x 19.7	5/16"
6" x 8" Cove Base Corner Right	5-7/8" x 7-3/4"	14.9 x 19.7	5/16"
1" x 6" Cove Base Inside Corner	1" x 5-7/8"	2.5 x 14.9	-
1" x 6" Cove Base Outside Corner	1" x 5-7/8"	2.5 x 14.9	-



6" x 8" Cove Base



6" x 8" Cove Base Corner Left



6" x 8" Cove Base Corner Right



Inside & Outside Base Corner

Shade & Texture Index

EcoCycle has a shade variation of V3.



V1



V2



V3



V4

V1=Uniform Appearance
V2=Slight Variation
V3=Moderate Variation
V4=Substantial Variation

EcoCycle EC001 has a shade variation of V1

Recommended Usage

EcoCycle is recommended for interior floors and walls and exterior walls in both commercial and residential applications. EcoCycle is not recommended for exterior horizontal use, with the exception of EC001 in the Cross-Tread finish, which is suitable for exterior horizontal surfaces and paving.

Care and Maintenance

Regular cleaning is the best way to keep EcoCycle tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at www.crossvilleinc.com.

Product Performance

	EcoCycle	EC001 (CTS only)	
Breaking Strength	>350 lbf.	>350 lbf.	ASTM C648
Bond Strength	>200 psi	>200 psi	ASTM C482
Chemical Resistance	Unaffected	Unaffected	ASTM C650
Frost Resistance	Resistant	Resistant	ASTM C1026
Water Absorption	<.10%	<.10%	ASTM C373
Scratch Hardness	7	6	MOH's Scale
COF-Dry	>0.65	>0.8	ASTM C1028-89
COF-Wet	>0.6	>0.8	ASTM C1028-89

